

# 160 Gallon 3000# WP Class VI 6-Station PLC Accumulator



**8356**

## BUILDING DIMENSIONS & WEIGHT

Length	20' 9"	6.32 m
Width	9' 6"	2.90 m
Height	9'	2.74 m
Weight	25,133 lbs	11,400 kgs

## ACCUMULATOR SPECIFICATIONS

Manufacturer:	Control Technology Inc.	
Operating Size:	160 US Gallons	
Classification:	Class VI 6-Station API 16-D Certified	
Maximum Accumulator Pressure:	3000 PSI / 20,685 kPa	
Recommended Manifold Pressure:	1500 PSI / 10,500 kPa	
Operating System:	Electric / Hydraulic PLC	
Precharge Volume:	(16) 11 US Gal. / (16) 41.6 L	
EUB Precharge Volume:	160 US Gal. / 605.67 L	
Usable Volume @ 3000 PSI:	80 US Gallons	
@ 20,685 kPa:	302.83 Litres	
Accumulator Precharge:	1000 PSI / 7000 kPa	
N2 Backup:	(6) 337 cu.ft. @ 2200 PSI	
	(6) 58 L @ 15,168 kPa	



## ELECTRICAL FEATURES

208 Volt, UPS Battery Back Up, 150' Data Cable  
 Pump #1 Cord -100 Amp, 4 wire, 4 pole Appleton x 84'  
 Pump #2 Cord -60 Amp, 4 wire, 4 pole Appleton x 91'

## HOSE FEATURES

Hose Length- 100' Hydraulic + 25' Fire Guard  
 5 Stations - 3/4" 3100 PSI  
 1 Station - 1/2" 3500 PSI



## PUMP FEATURES

<u>Pump #1</u>	Cat 660 Triplex	Output:	9.5 US GPM
<u>Pump #2</u>	Pratissoli Triplex	Output:	12.5 US GPM

## SUPPLEMENTARY SUPPLIES

- (1) Nitrogen Pre-charge Kit
- (4) Hose Cone Stands



## Circle T Service & Rental Ltd.

8012 Edgar Industrial Green, Red Deer, Alberta T4P 3S2  
 403.342.6004  
 circletrentals.com